



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

1 / 11

In conformity to Regulation (EU) 2015/830

SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code : CHAIN GREASE
Trades code : 50150-DK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricant
Sectors of use:
Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]
Product category:
Lubricants, Greases and Release Products

Uses advised against
Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Super Help srl - Via V.Veneto, 11 - 21100 Varese (VA) - Italy Tel. + 39 347/4650120 Fax +39 0331/953178
Email: info@super-help.com – Web: www.super-help.com

1.4. Emergency telephone number

National contact: Emergency telephon number EU 112

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS02, GHS07, GHS08

Hazard Class and Category Code(s):
Flam. Aerosol 1, STOT SE 3, Asp. Tox. 1

Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H304 - May be fatal if swallowed and enters airways.
H336 - May cause drowsiness or dizziness.

Aerosol that ignites easily even at low temperatures, fire risk
Warning: Vapours inhalation may cause sleepiness and giddiness
The repeated inhalation of vapors can cause drowsiness and giddiness.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

2 / 11

In conformity to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS02, GHS07 - Danger



Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H336 - May cause drowsiness or dizziness.

Supplemental Hazard statement Code(s):
EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements:
General

P102 - Keep out of reach of children.
Prevention
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.

Storage
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains:
1,2-dichloropropane, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements
Hydrocarbons, C3-4 contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Hydrocarbons, C3-4	> 50 <= 100%	Flam. Gas 1, H220; Press. Gas, H280	649-199-00-1	68476-40-4	270-681-9	01- 2119486557
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	> 30 <= 50%	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336			919-857-5	01- 2119463258 -33
1,2-dichloropropane	> 0,9 <= 4,9%	Flam. Liq. 2, H225; Acute Tox. 4, H302;	602-020-00-0	78-87-5	201-152-2	01- 2119557878 -16



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

3 / 11

In conformity to Regulation (EU) 2015/830

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
		Acute Tox. 4, H332				

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room. CALL A PHYSICIAN.

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

If breathing has stopped, give artificial respiration.

Direct contact with skin (of the pure product):

Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water for at least 10 minutes.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to substances refer to paragraph 11.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

Call a POISON CENTER or a doctor if you feel unwell.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:

Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

4 / 11

In conformity to Regulation (EU) 2015/830

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke
Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.
Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.
However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.
Wear suitable gloves (PVC, butyl rubber, neoprene or similar) and protective clothing.
Eliminate all unguarded flames and possible sources of ignition. No smoking.
Provision of sufficient ventilation.
Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill
Inform the competent authorities.
Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors
Use extreme caution when handling the product. Avoid shock or friction.
In residential areas do not use on large surfaces.
Do not smoke at work
At work do not eat or drink.
Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

5 / 11

In conformity to Regulation (EU) 2015/830

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Private households (= general public = consumers):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

Public domain (administration, education, entertainment, services, craftsmen):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

Hydrocarbons, C3-4:

TLV-TWA: 1000 ppm (ACGIH 2010)

MAK: 1000 ppm 2400 mg/m³

Peak limitation category: II(4)

Pregnancy risk group: D (DFG 2008)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

TLV-TWA: 1200 mg/m³, 197 ppm (ACGIH)

1,2-dichloropropane:

TLV-TWA: 10 ppm (ACGIH 2013)

A4 (not classifiable as a human carcinogen)

MAK: Carcinogen category 3B (DFG 2006)

- Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

DNEL

Systemic effects Long term Workers inhalation = 8710 (mg/m³)

Systemic effects Long term Workers dermal = 208 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 185 (mg/m³)

Systemic effects Long term Consumers dermal = 125 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 125 (mg/kg bw/day)

- Substance: 1,2-dichloropropane

DNEL

Systemic effects Long term Workers inhalation = 28,88 (mg/m³)

Systemic effects Long term Workers dermal = 1,03 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 14,44 (mg/m³)

Systemic effects Long term Consumers dermal = 0,52 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 0,52 (mg/kg bw/day)



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

6 / 11

In conformity to Regulation (EU) 2015/830

PNEC

Sweet water = 0,082 (mg/l)
sediment Sweet water = 0,157 (mg/kg/sediment)
Sea water = 0,0082 (mg/l)
sediment Sea water = 0,0157 (mg/kg/sediment)
intermittent emissions = 0,53 (mg/l)
STP = 0,53 (mg/l)
ground = 0,0284 (mg/kg ground)

8.2. Exposure controls

Appropriate engineering controls:

Private households (= general public = consumers):

Work in a well ventilated place or equipped with ventilation devices. Do not use on hot surfaces or surfaces exposed to sunlight in order to avoid rapid evaporation of the product. Use personal protective equipment (see below).

Public domain (administration, education, entertainment, services, craftsmen):

The use of appropriate technical measures should always take priority over personal protective equipment. Ensure good ventilation in the workplace through effective local aspiration. If these steps are not enough to maintain the concentration of the product below the exposure limit values in the workplace, wear appropriate respiratory protection. Provide a system for eye wash. Before using the product refer to the label for hazard details. During the selection of personal protective equipment, seek appropriate advice from the supplier. Personal protective equipment must comply with regulations in force.

Individual protection measures:

(a) Eye / face protection

Wear mask

(b) Skin protection

(i) Hand protection

Gloves material: nitrile

Thickness: 0,40 mm

Breakthrough time: > 480 min

(ii) Other

Avoid direct contact with the skin

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

Where the OEL may be approached or exceeded, wear mask with AX or universal filter.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.



SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
----------------------------------	-------	----------------------



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

7 / 11

In conformity to Regulation (EU) 2015/830

Physical and chemical properties	Value	Determination method
Appearance	brown liquid under pressure	VISUAL
Odour	characteristic	ORGANOLEPTIC
Odour threshold	not determined	
pH	irrelevant	PH-METER
Melting point/freezing point	< -100 °C (liquid gas)	
Initial boiling point and boiling range	> -42 °C (liquid gas)	
Flash point	< -80 °C (liquid gas)	
Evaporation rate	not determined	
Flammability (solid, gas)	irrelevant	
Upper/lower flammability or explosive limits	LEL 1,8% (vol); UEL 9,5% (vol)	
Vapour pressure	3,2 bar	
Vapour density	> 2 (liquid gas)	
Relative density	0,65 – 0,70 kg/l	
Solubility	in common organic solvents	
Water solubility	negligible	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	> 400 °C (liquid gas)	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not determined	
Oxidising properties	not determined	
Container volume	210 ml	ISO 90-3:2000
Product volume	150 ml	ISO 90-3:2000
Pressure to 20 °C	3,2 bar	
Deformation pressure	16,5 bar	MANOMETER GAUGE
Burst pressure of the container	18 bar	MANOMETER GAUGE
Flash point of liquid phase	< 21 °C	
Propellant inflammability	< 0 °C	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Related to contained substances:

1,2-dichloropropane:

On combustion, forms toxic and corrosive fumes. Attacks aluminum alloys and some types of plastics.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

8 / 11

In conformity to Regulation (EU) 2015/830

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 °C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = 47.509,5 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = 37,5 mg/l/4 h

(a) acute toxicity: based on available data, the classification criteria are not met.

(b) skin corrosion/irritation based on available data, the classification criteria are not met.

(c) serious eye damage/irritation: based on available data, the classification criteria are not met.

(d) respiratory or skin sensitization: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: based on available data, the classification criteria are not met.

(h) specific target organ toxicity (STOT) single exposure: Warning: Vapours inhalation may cause sleepiness and giddiness

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Hydrocarbons, C3-4:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation.

INHALATION RISK: On loss of containment this liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in confined areas.

EFFECTS OF SHORT-TERM EXPOSURE: Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system.

ACUTE HAZARDS/SYMPTOMS

INHALATION Drowsiness. Unconsciousness.

SKIN ON CONTACT WITH LIQUID: FROSTBITE.

EYES ON CONTACT WITH LIQUID: FROSTBITE.

N O T E S High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

INHALATION RISK: No indication can be given about the rate in which a harmful concentration in the air is reached on evaporation of this substance at 20 °C.



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

9 / 11

In conformity to Regulation (EU) 2015/830

EFFECTS OF SHORT-TERM EXPOSURE: The vapour is slightly irritating to the eyes. The substance may cause effects on the central nervous system. Exposure to high concentration of vapours may result in unconsciousness. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin.

ACUTE HAZARDS/SYMPTOMS

INHALATION Dizziness. Headache. Drowsiness. Nausea. Unconsciousness.

SKIN Dry skin.

EYES Redness. Pain.

INGESTION Cough. Diarrhoea. Sore throat. Vomiting. (Further see Inhalation).

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5000

1,2-dichloropropane:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation and by ingestion.

INHALATION RISK: A harmful contamination of the air can be reached rather quickly on evaporation of this substance at 20 °C.

EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes, the skin and the respiratory tract. The substance may cause effects on the central nervous system.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin. Substance may have effects on the liver and kidneys.

ACUTE HAZARDS/SYMPTOMS

INHALATION Cough. Dizziness. Drowsiness. Headache. Sore throat.

SKIN Dry skin. Redness. Pain.

EYES Redness. Pain.

INGESTION Abdominal pain. Diarrhoea. Drowsiness. Headache. Nausea. Vomiting.

LD50 (rat) Oral (mg/kg body weight) = 1900

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 8750

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Hydrocarbons, C3-4:

Toxicity to daphnia and other aquatic invertebrates

- LC50 Daphnia magna, 48h = 14,22 mg/l (butane)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish

- LC50 Oncorhynchus mykiss (rainbow trout), 96h > 1000 mg/l (literature value)

Toxicity to daphnia and other aquatic invertebrates

- EC50 Daphnia magna, 48h = 1000 mg/l

Toxicity to algae

- EC50 Pseudokirchnerella subcapitata, 72h > 1000 mg/l (literature value)

1,2-dichloropropane:

Toxicity to fish

- LC50 Pimephales promelas, 96h = 127 mg/l

Toxicity to daphnia and other aquatic invertebrates

- EC50 Daphnia magna, 24h = 11,5 mg/l

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

10 / 11

In conformity to Regulation (EU) 2015/830

12.3. Bioaccumulative potential

Related to contained substances:

Hydrocarbons, C3-4:

1.09 to 2.80 log Pow (liquefied petroleum gas)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 °C can burst.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number

1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

AEROSOL flammable

14.3. Transport hazard class(es)

Class: 2

Label: Onu

Tunnel restriction code : D

Limited quantities : 1 L

EmS : F-D, S-U

14.4. Packing group

--

14.5. Environmental hazards

Product is not environmentally hazardous

Marine polluting agent: Not



SAFETY DATA SHEET

CHAIN GREASE

Issued on 01/17/2011 - Rel. # 3 on 03/31/2016

11 / 11

In conformity to Regulation (EU) 2015/830

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions.
The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 96/82/EC (Seveso), annex I, part 2: category 8

Control of Substances Hazardous to Health (COSHH), Regulations 2002

Regulation 2006/1907/EC (REACH), Regulation 2008/1272/EC (CLP), Regulation 2009/790/EC.

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Description of the hazard statements exposed to point 3

H220 = Extremely flammable gas.

H280 = Contains gas under pressure; may explode if heated.

H226 = Flammable liquid and vapour.

H304 = May be fatal if swallowed and enters airways.

H336 = May cause drowsiness or dizziness.

H225 = Highly flammable liquid and vapour.

H302 = Harmful if swallowed.

H332 = Harmful if inhaled.

Classification based on data of all mixture components

Main normative references:

Directive 67/548/EEC (29th adaptation)

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

*** This tab annuls and replaces any previous edition.