



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 1 / 12

In conformity to Regulation (EU) 2015/830

### SECTION1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product code: SUPER HELP - LITHIUM GREASE  
Trades code: 26400

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricant

Sectors of use:

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Lubricants, Greases and Release Products

Uses advised against

Do not use for purposes other than those listed

#### 1.3. Details of the supplier of the safety data sheet

Super Help srl - Via V.Veneto, 11 - 21100 Varese (VA) - Italy Tel. + 39 347/4650120 Fax +39 0331/953178

Email: [info@super-help.com](mailto:info@super-help.com) – Web: [www.super-help.com](http://www.super-help.com)

#### 1.4. Emergency telephone number

National contact: Emergency telephon number EU 112

### SECTION2. Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS02, GHS07, GHS08

Hazard Class and Category Code(s):

Flam. Aerosol 1, STOT SE 3, Asp. Tox. 1

Hazard statement Code(s):

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H304 - May be fatal if swallowed and enters airways.

H336 - May cause drowsiness or dizziness.

Aerosol that ignites easily even at low temperatures, fire risk

Warning: Vapours inhalation may cause sleepiness and giddiness

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 2 / 12

In conformity to Regulation (EU) 2015/830

### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):  
GHS02, GHS07 - Danger



Hazard statement Code(s):  
H222 - Extremely flammable aerosol.  
H229 - Pressurized container: May burst if heated.  
H336 - May cause drowsiness or dizziness.

Supplemental Hazard statement Code(s):  
not applicable

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P271 - Use only outdoors or in a well-ventilated area.

Storage

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### 2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

## SECTION 3. Composition/information on ingredients

### 3.1 Substances

Irrilevant

### 3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Hydrocarbons, C3-4 contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

| Substance  | Concentration | Classification   | Index        | CAS        | EINECS    | REACH                    |
|--|---------------|--|--------------|------------|-----------|--------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | > 30 <= 50%   | Flam. Liq. 3, H226;<br>Asp. Tox. 1, H304;<br>STOT SE 3, H336 |              |            | 919-857-5 | 01-<br>2119463258<br>-33 |
| Hydrocarbons, C3-4   | > 24 <= 30%   | Flam. Gas 1, H220;<br>Press. Gas, H280                       | 649-199-00-1 | 68476-40-4 | 270-681-9 | 01-<br>2119486557<br>-00 |
| 1,2-dichloropropane  | > 4,9 <= 9,5% | Flam. Liq. 2, H225;<br>Acute Tox. 4, H302;                   | 602-020-00-0 | 78-87-5    | 201-152-2 | 01-<br>2119557878<br>-16 |



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 3 / 12

In conformity to Regulation (EU) 2015/830

| Substance | Concentration | Classification     | Index | CAS | EINECS | REACH |
|-----------|---------------|--------------------|-------|-----|--------|-------|
|           |               | Acute Tox. 4, H332 |       |     |        |       |

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room. CALL A PHYSICIAN.

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

If breathing has stopped, give artificial respiration.

##### Direct contact with skin (of the pure product):

Wash thoroughly with soap and running water.

##### Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water for at least 10 minutes.

##### Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

#### 4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to substances refer to paragraph 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

Call a POISON CENTER or a doctor if you feel unwell.

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### Advised extinguishing agents:

CO2 or dry powder extinguisher

##### Extinguishing means to avoid:

Direct jets of water

#### 5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

#### 5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 4 / 12

In conformity to Regulation (EU) 2015/830

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear suitable gloves (PVC, butyl rubber, neoprene or similar) and protective clothing.

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

#### 6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

#### 6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

#### 6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Use extreme caution when handling the product. Avoid shock or friction.

In residential areas do not use on large surfaces.

Do not smoke at work

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

See also paragraph 8 below.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 5 / 12

In conformity to Regulation (EU) 2015/830

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

### 7.3. Specific end use(s)

Private households (= general public = consumers):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

Public domain (administration, education, entertainment, services, craftsmen):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Related to contained substances:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:  
TLV-TWA: 1200 mg/m<sup>3</sup>, 197 ppm (ACGIH)

Hydrocarbons, C3-4:

TLV-TWA: 1000 ppm (ACGIH 2010)  
MAK: 1000 ppm 2400 mg/m<sup>3</sup>  
Peak limitation category: II(4)  
Pregnancy risk group: D (DFG 2008)

1,2-dichloropropane:

TLV-TWA: 10 ppm (ACGIH 2013)  
A4 (not classifiable as a human carcinogen)  
MAK: Carcinogen category 3B (DFG 2006)

- Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
DNEL

Systemic effects Long term Workers inhalation = 8710 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 208 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 185 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 125 (mg/kg bw/day)  
Systemic effects Long term Consumers oral = 125 (mg/kg bw/day)

- Substance: 1,2-dichloropropane

DNEL  
Systemic effects Long term Workers inhalation = 28,88 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 1,03 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 14,44 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 0,52 (mg/kg bw/day)



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 6 / 12

In conformity to Regulation (EU) 2015/830

Systemic effects Long term Consumers oral = 0,52 (mg/kg bw/day)

PNEC

Sweet water = 0,082 (mg/l)

sediment Sweet water = 0,157 (mg/kg/sediment)

Sea water = 0,0082 (mg/l)

sediment Sea water = 0,0157 (mg/kg/sediment)

intermittent emissions = 0,53 (mg/l)

STP = 0,53 (mg/l)

ground = 0,0284 (mg/kg ground)

### 8.2. Exposure controls



Appropriate engineering controls:

Private households (= general public = consumers):

Work in a well ventilated place or equipped with ventilation devices. Do not use on hot surfaces or surfaces exposed to sunlight in order to avoid rapid evaporation of the product. Use personal protective equipment (see below).

Public domain (administration, education, entertainment, services, craftsmen):

The use of appropriate technical measures should always take priority over personal protective equipment. Ensure good ventilation in the workplace through effective local aspiration. If these steps are not enough to maintain the concentration of the product below the exposure limit values in the workplace, wear appropriate respiratory protection. Provide a system for eye wash. Before using the product refer to the label for hazard details. During the selection of personal protective equipment, seek appropriate advice from the supplier. Personal protective equipment must comply with regulations in force.

Individual protection measures:

(a) Eye / face protection

Wear mask

(b) Skin protection

(i) Hand protection

Gloves material: nitrile

Thickness: 0,40 mm

Breakthrough time: > 480 min

(ii) Other

Avoid direct contact with the skin

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

Where the OEL may be approached or exceeded, wear mask with combined AX-P filter.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

## SECTION9. Physical and chemical properties



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 7 / 12

In conformity to Regulation (EU) 2015/830

### 9.1. Information on basic physical and chemical properties

| Physical and chemical properties             | Value                          | Determination method |
|--|--------------------------------|----------------------|
| Appearance                                   | brown liquid under pressure    | VISUAL               |
| Odour  | characteristic                 | ORGANOLEPTIC         |
| Odour threshold                              | not determined                 |                      |
| pH   | irrelevant                     | PH-METER             |
| Melting point/freezing point                 | < -100 °C (liquid gas)         |                      |
| Initial boiling point and boiling range      | > -42 °C (liquid gas)          |                      |
| Flash point                                  | < -80 °C (liquid gas)          |                      |
| Evaporation rate                             | not determined                 |                      |
| Flammability (solid, gas)                    | irrelevant                     |                      |
| Upper/lower flammability or explosive limits | LEL 1,8% (vol); UEL 9,5% (vol) |                      |
| Vapour pressure                              | 3,2 bar                        |                      |
| Vapour density                               | > 2 (liquid gas)               |                      |
| Relative density                             | 0,65 – 0,70 kg/l               |                      |
| Solubility                                   | in common organic solvents     |                      |
| Water solubility                             | negligible                     |                      |
| Partition coefficient: n-octanol/water       | not determined                 |                      |
| Auto-ignition temperature                    | > 400 °C (liquid gas)          |                      |
| Decomposition temperature                    | not determined                 |                      |
| Viscosity                                    | not determined                 |                      |
| Explosive properties                         | not determined                 |                      |
| Oxidising properties                         | not determined                 |                      |
| Container volume                             | 520 ml                         | ISO 90-3:2000        |
| Product volume                               | 400 ml                         | ISO 90-3:2000        |
| Pressure to 20 °C                            | 3,2 bar                        |                      |
| Deformation pressure                         | 16,5 bar                       | MANOMETER GAUGE      |
| Burst pressure of the container              | 18 bar                         | MANOMETER GAUGE      |
| Flash point of liquid phase                  | < 21 °C                        |                      |
| Propellant inflammability                    | < 0 °C                         |                      |

### 9.2. Other information

No data available.

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

Related to contained substances:

1,2-dichloropropane:

On combustion, forms toxic and corrosive fumes. Attacks aluminum alloys and some types of plastics.

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.



## SAFETY DATA SHEET

### SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 8 / 12

In conformity to Regulation (EU) 2015/830

#### 10.3. Possibility of hazardous reactions

There are no hazardous reactions

#### 10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire. heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 °C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

#### 10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

#### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11. Toxicological information

### 11.1. Information on toxicological effects

ATE(mix) oral = 37.981,0 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = 30,0 mg/l/4 h

(a) acute toxicity: based on available data, the classification criteria are not met.

(b) skin corrosion/irritation based on available data, the classification criteria are not met.

(c) serious eye damage/irritation: based on available data, the classification criteria are not met.

(d) respiratory or skin sensitization: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: based on available data, the classification criteria are not met.

(h) specific target organ toxicity (STOT) single exposure: Warning: Vapours inhalation may cause sleepiness and giddiness

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

INHALATION RISK: No indication can be given about the rate in which a harmful concentration in the air is reached on evaporation of this substance at 20 °C.

EFFECTS OF SHORT-TERM EXPOSURE: The vapour is slightly irritating to the eyes. The substance may cause effects on the central nervous system. Exposure to high concentration of vapours may result in unconsciousness. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin.

ACUTE HAZARDS/SYMPTOMS

INHALATION Dizziness. Headache. Drowsiness. Nausea. Unconsciousness.

SKIN Dry skin.

EYES Redness. Pain.





# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 9 / 12

In conformity to Regulation (EU) 2015/830

INGESTION Cough. Diarrhoea. Sore throat. Vomiting. (Further see Inhalation).  
LD50 (rat) Oral (mg/kg body weight) = 5000  
LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000  
CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5000

Hydrocarbons, C3-4:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation.

INHALATION RISK: On loss of containment this liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in confined areas.

EFFECTS OF SHORT-TERM EXPOSURE: Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system.

ACUTE HAZARDS/SYMPTOMS

INHALATION Drowsiness. Unconsciousness.

SKIN ON CONTACT WITH LIQUID: FROSTBITE.

EYES ON CONTACT WITH LIQUID: FROSTBITE.

N O T E S High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death.

1,2-dichloropropane:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation and by ingestion.

INHALATION RISK: A harmful contamination of the air can be reached rather quickly on evaporation of this substance at 20 °C.

EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes, the skin and the respiratory tract. The substance may cause effects on the central nervous system.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin. Substance may have effects on the liver and kidneys.

ACUTE HAZARDS/SYMPTOMS

INHALATION Cough. Dizziness. Drowsiness. Headache. Sore throat.

SKIN Dry skin. Redness. Pain.

EYES Redness. Pain.

INGESTION Abdominal pain. Diarrhoea. Drowsiness. Headache. Nausea. Vomiting.

LD50 (rat) Oral (mg/kg body weight) = 1900

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 8750

## SECTION 12. Ecological information

### 12.1. Toxicity

Related to contained substances:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish

- LC50 *Oncorhynchus mykiss* (rainbow trout), 96h > 1000 mg/l (literature value)

Toxicity to daphnia and other aquatic invertebrates

- EC50 *Daphnia magna*, 48h = 1000 mg/l

Toxicity to algae

- EC50 *Pseudokirchnerella subcapitata*, 72h > 1000 mg/l (literature value)

Hydrocarbons, C3-4:

Toxicity to daphnia and other aquatic invertebrates

- LC50 *Daphnia magna*, 48h = 14,22 mg/l (butane)

1,2-dichloropropane:

Toxicity to fish

- LC50 *Pimephales promelas*, 96h = 127 mg/l

Toxicity to daphnia and other aquatic invertebrates

- EC50 *Daphnia magna*, 24h = 11,5 mg/l

Use according to good working practices to avoid pollution into the environment.



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 10 / 12

In conformity to Regulation (EU) 2015/830

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

Related to contained substances:

Hydrocarbons, C3-4:

1.09 to 2.80 log Pow (liquefied petroleum gas)

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

### 12.6. Other adverse effects

No adverse effects

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 °C can burst.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

## SECTION 14. Transport information

### 14.1. UN number

1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



### 14.2. UN proper shipping name

AEROSOL flammable

### 14.3. Transport hazard class(es)

Class: 2

Label: Onu

Tunnel restriction code : D

Limited quantities : 1 L

EmS : F-D, S-U

### 14.4. Packing group

--



# SAFETY DATA SHEET

## SUPER HELP - LITHIUM GREASE

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 11 / 12

In conformity to Regulation (EU) 2015/830

### 14.5. Environmental hazards

Product is not environmentally hazardous  
Marine polluting agent: Not

### 14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions.  
The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU, annex I, part 1

Control of Substances Hazardous to Health (COSHH), Regulations 2002

Regulation 2006/1907/EC (REACH), Regulation 2008/1272/EC (CLP).

### 15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

## SECTION 16. Other information

### 16.1. Other information

Points modified compared to previous release: 1.2. Relevant identified uses of the substance or mixture and uses advised against, 2.1. Classification of the substance or mixture, 2.2. Label elements, 2.3. Other hazards, 3.1 Substances, 3.2 Mixtures, 4.1. Description of first aid measures, 4.3. Indication of any immediate medical attention and special treatment needed, 5.1. Extinguishing media, 6.1. Personal precautions, protective equipment and emergency procedures, 7.1. Precautions for safe handling, 7.2. Conditions for safe storage, including any incompatibilities, 7.3. Specific end use(s), 8.1. Control parameters, 8.2. Exposure controls, 10.1. Reactivity, 10.4. Conditions to avoid, 11.1. Information on toxicological effects, 12.1. Toxicity, 12.3. Bioaccumulative potential, 14.3. Transport hazard class(es), 14.5. Environmental hazards, 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

H226 = Flammable liquid and vapour.

H304 = May be fatal if swallowed and enters airways.

H336 = May cause drowsiness or dizziness.

H220 = Extremely flammable gas.

H280 = Contains gas under pressure; may explode if heated.

H225 = Highly flammable liquid and vapour.

H302 = Harmful if swallowed.

H332 = Harmful if inhaled.

Classification based on data of all mixture components

Main normative references:

Regulation 1907/2006/EC

Regulation 1272/2008/EC



**SAFETY DATA SHEET**  
**SUPER HELP - LITHIUM GREASE**

Issued on 01/17/2011 - Rel. # 2 on 05/05/2016

# 12 / 12

In conformity to Regulation (EU) 2015/830

---

Regulation (EU) 2015/830

\*\*\* This tab annuls and replaces any previous edition.