



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

1 / 13

In conformity to Regulation (EU) 2015/830

SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code: SUPER HELP - BIKE DEGREASER
Trades code: 840

1.2. Relevant identified uses of the substance or mixture and uses advised against

Solvent detergent for mechanics parts

Sectors of use:

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Washing and Cleaning Products (including solvent based products)

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Super Help srl - Via V.Veneto, 11 - 21100 Varese (VA) - Italy Tel. + 39 347/4650120

Email: info@super-help.com – Web: www.super-help.com

1.4. Emergency telephone number

National contact: Emergency telephon number EU 112

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS02, GHS07, GHS08

Hazard Class and Category Code(s):

Flam. Aerosol 1, Eye Irrit. 2, STOT SE 3, Asp. Tox. 1

Hazard statement Code(s):

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H304 - May be fatal if swallowed and enters airways.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Aerosol that ignites easily even at low temperatures, fire risk

If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

Warning: Vapours inhalation may cause sleepiness and giddiness

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

2 / 13

In conformity to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS02, GHS07 - Danger



Hazard statement Code(s):
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Supplemental Hazard statement Code(s):
not applicable

Precautionary statements:

General

P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

Storage

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, propan-2-ol

Contains (Reg.EC 648/2004):

> 30% aliphatic hydrocarbons

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Hydrocarbons, C3-4 contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

3 / 13

In conformity to Regulation (EU) 2015/830

Note H - The classification and labelling shown for this substance applies to the hazardous property(ies) indicated by the hazard statement(s) in combination with the hazard class(es) and category(ies) shown. The requirements of Article 4 for manufacturers, importers or downstream users of this substance apply to all other hazard classes and categories. For hazard classes where the route of exposure or the nature of the effects leads to a differentiation of the classification of the hazard class, the manufacturer, importer or downstream user is required to consider the routes of exposure or the nature of the effects not already considered. The final label shall follow the requirements of Article 17 and of section 1.2 of Annex I.

Note K - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
Hydrocarbons, C3-4 Note: H K U	> 30 <= 50%	Flam. Gas 1, H220; Press. Gas, H280	649-199-00-1	68476-40-4	270-681-9	01-211948 6557-22
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	> 30 <= 50%	EUH066; Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336			919-857-5	01-211946 3258-33
propan-2-ol	> 9,5 <= 15%	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	603-117-00-0	67-63-0	200-661-7	01-211945 7558-25
ethyl alcohol	> 0,9 <= 4,9%	Flam. Liq. 2, H225; Eye Irrit. 2, H319	603-002-00-5	64-17-5	200-578-6	01-211945 7610-43

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to substances refer to paragraph 11.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

4 / 13

In conformity to Regulation (EU) 2015/830

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:
CO₂ or dry powder extinguisher

Extinguishing means to avoid:
Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheat, burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.
Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus
Safety helmet and full protective suit.
The spray water can be used to protect the people involved in the extinction
You may also use self-respirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211, Fluobrene, Solkan 123, NAF, etc...)
Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:
Leave the area surrounding the spill or release. Do not smoke
Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.
Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:
Given the tightness of aerosol, it is unlikely that the spillage may occur.
However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.
Wear mask, gloves and protective clothing.
Eliminate all unguarded flames and possible sources of ignition. No smoking.
Provision of sufficient ventilation.
Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill
Inform the competent authorities.
Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:
Rapidly recover the product, wear a mask and protective clothing
Recover the product for reuse, if possible, or the removal.



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

5 / 13

In conformity to Regulation (EU) 2015/830

6.3.2 For cleaning up:
After wiping up, wash with water the area and materials involved

6.3.3 Other information:
None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors
Wear protective gloves/protective clothing/eye protection/face protection.
Use extreme caution when handling the product. Avoid shock or friction.
In residential areas do not use on large surfaces.
Do not smoke at work
At work do not eat or drink.
Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.
Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Private households (= general public = consumers):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

Public domain (administration, education, entertainment, services, craftsmen):

- Keep away from heat sources, sparks, open flames
- Do not use on hot surfaces or surfaces exposed to direct sunlight
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Accumulations of flammable gas in the air may occur in case of an excessive use
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

6 / 13

In conformity to Regulation (EU) 2015/830

Hydrocarbons, C3-4:
TLV-TWA: 1000 ppm (ACGIH 2010)
MAK: 1000 ppm 2400 mg/m³
Peak limitation category: II(4)
Pregnancy risk group: D (DFG 2008)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:
TLV-TWA: 1200 mg/m³, 197 ppm (ACGIH)

propan-2-ol:
TLV-TWA: 200 ppm
TLV-STEL: 400 ppm
A4 (not classifiable as a human carcinogen) (ACGIH 2013)
MAK: 200 ppm, 500 mg/m³
Peak limitation category: II(2)
Pregnancy risk group: C (DFG 2004)

ethyl alcohol:
TLV-TWA: 1000 ppm - 1880 mg/m³ (A4)
Not classifiable as a human carcinogen (ACGIH 2013)
MAK: 500 ppm - 960 mg/m³
Peak limitation category: II(2)
Carcinogen category: 5
Pregnancy risk group: C
Germ cell mutagen group: 5 (DFG 2004)

- Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
DNEL
Systemic effects Long term Workers inhalation = 8710 (mg/m³)
Systemic effects Long term Workers dermal = 208 (mg/kg bw/day)
Systemic effects Long term Consumers inhalation = 185 (mg/m³)
Systemic effects Long term Consumers dermal = 125 (mg/kg bw/day)
Systemic effects Long term Consumers oral = 125 (mg/kg bw/day)

- Substance: propan-2-ol
DNEL
Systemic effects Long term Workers inhalation = 500 (mg/m³)
Systemic effects Long term Workers dermal = 880 (mg/kg bw/day)
Systemic effects Long term Consumers inhalation = 89 (mg/m³)
Systemic effects Long term Consumers dermal = 319 (mg/kg bw/day)
Systemic effects Long term Consumers oral = 26 (mg/kg bw/day)
PNEC
Sweet water = 140,9 (mg/l)
sediment Sweet water = 552 (mg/kg/sediment)
Sea water = 140,9 (mg/l)
sediment Sea water = 552 (mg/kg/sediment)
ground = 28 (mg/kg ground)

- Substance: ethyl alcohol
DNEL
Systemic effects Long term Workers inhalation = 950 (mg/m³)
Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)
Local effects Short term Workers inhalation = 1900 (mg/m³)
PNEC
Sweet water = 0,96 (mg/l)
sediment Sweet water = 3,6 (mg/kg/sediment)
Sea water = 0,79 (mg/l)
sediment Sea water = 2,9 (mg/kg/sediment)



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

7 / 13

In conformity to Regulation (EU) 2015/830

STP = 580 (mg/l)
ground = 0,63 (mg/kg ground)

8.2. Exposure controls



Appropriate engineering controls:
Private households (= general public = consumers):
Work in a well ventilated place or equipped with ventilation devices. Do not use on hot surfaces or surfaces exposed to sunlight in order to avoid rapid evaporation of the product. Use personal protective equipment (see below).

Public domain (administration, education, entertainment, services, craftsmen):
Ensure good ventilation in the workplace through effective local aspiration. If these steps are not enough to maintain the concentration of the product below the exposure limit values in the workplace, wear appropriate respiratory protection. Provide a system for eye wash. Before using the product refer to the label for hazard details. During the selection of personal protective equipment, seek appropriate advice from the supplier. Personal protective equipment must comply with regulations in force.

Individual protection measures:

(a) Eye / face protection
Wear mask

(b) Skin protection

(i) Hand protection
Gloves material: nitrile
Thickness: 0,40 mm
Breakthrough time: > 480 min

(ii) Other
When handling the pure product wear full protective skin clothing.
Better is to use cotton antistatic clothing

(c) Respiratory protection
Work in a sufficiently ventilated to avoid inhaling the product.
Where the OEL may be approached or exceeded, wear mask with AX or universal filter.

(d) Thermal hazards
No hazard to report

Environmental exposure controls:
Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	colorless liquid under pressure	VISUAL
Odour	typical	ORGANOLEPTIC
Odour threshold	not determined	
pH	irrelevant	PH-METER
Melting point/freezing point	< -100 °C (drivgas)	



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

8 / 13

In conformity to Regulation (EU) 2015/830

Physical and chemical properties	Value	Determination method
Initial boiling point and boiling range	> -42 °C (drivgas)	
Flash point	< -80 °C (drivgas)	
Evaporation rate	not determined	
Flammability (solid, gas)	not determined	
Upper/lower flammability or explosive limits	LEL 1,8% (vol); UEL 9,5% (vol)	
Vapour pressure	3,2 bar	
Vapour density	> 2 (drivgas)	
Relative density	0,62-0,67 kg/l	
Solubility	in common organic solvents	
Water solubility	negligible	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	> 400 °C (drivgas)	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not determined	
Oxidising properties	not determined	
Container volume	520 ml	ISO 90-3:2000
Product volume	400 ml	ISO 90-3:2000
Pressure to 20 °C	3,2 bar	
Deformation pressure	16,5 bar	MANOMETER GAUGE
Burst pressure of the container	18 bar	MANOMETER GAUGE
Flash point of liquid phase	< 55 °C	
Propellent inflammability	< 0 °C	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Related to contained substances:

propan-2-ol:

Reacts with strong oxidants. Attacks some plastic, rubber.

ethyl alcohol:

Reacts slowly with calcium hypochlorite, silver oxide and ammonia, causing fire and explosion hazard. Reacts violently with strong oxidants such as nitric acid, silver nitrate, mercuric nitrate or magnesium perchlorate, causing fire and explosion hazard.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

9 / 13

In conformity to Regulation (EU) 2015/830

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 °C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = ∞

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: based on available data, the classification criteria are not met.

(b) skin corrosion/irritation based on available data, the classification criteria are not met.

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

(d) respiratory or skin sensitization: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: based on available data, the classification criteria are not met.

(h) specific target organ toxicity (STOT) single exposure: Warning: Vapours inhalation may cause sleepiness and giddiness

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Hydrocarbons, C3-4:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation.

INHALATION RISK: On loss of containment this liquid evaporates very quickly displacing the air and causing a serious risk of suffocation when in confined areas.

EFFECTS OF SHORT-TERM EXPOSURE: Rapid evaporation of the liquid may cause frostbite. The substance may cause effects on the central nervous system.

ACUTE HAZARDS/SYMPTOMS

INHALATION Drowsiness. Unconsciousness.

SKIN ON CONTACT WITH LIQUID: FROSTBITE.

EYES ON CONTACT WITH LIQUID: FROSTBITE.

N O T E S High concentrations in the air cause a deficiency of oxygen with the risk of unconsciousness or death.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

INHALATION RISK: No indication can be given about the rate in which a harmful concentration in the air is reached on



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

10 / 13

In conformity to Regulation (EU) 2015/830

evaporation of this substance at 20 °C.

EFFECTS OF SHORT-TERM EXPOSURE: The vapour is slightly irritating to the eyes. The substance may cause effects on the central nervous system. Exposure to high concentration of vapours may result in unconsciousness. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin.

ACUTE HAZARDS/SYMPTOMS

INHALATION Dizziness. Headache. Drowsiness. Nausea. Unconsciousness.

SKIN Dry skin.

EYES Redness. Pain.

INGESTION Cough. Diarrhoea. Sore throat. Vomiting. (Further see Inhalation).

LD50 (rat) Oral (mg/kg body weight) = 5000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 5000

propan-2-ol:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour.

INHALATION RISK: A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C; on spraying or dispersing, however, much faster.

EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes and the respiratory tract. The substance may cause effects on the central nervous system, resulting in depression. Exposure far above the OEL may result in unconsciousness.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin.

ACUTE HAZARDS/SYMPTOMS

INHALATION Cough. Dizziness. Drowsiness. Headache. Sore throat. (See Ingestion).

SKIN Dry skin.

EYES Redness.

INGESTION Abdominal pain. Laboured breathing. Nausea. Unconsciousness. Vomiting. (Further see Inhalation).

N O T E S Use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 2100

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

ethyl alcohol:

ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

INHALATION RISK: A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C.

EFFECTS OF SHORT-TERM EXPOSURE: The substance irritates the eyes. Inhalation of high concentration of vapour may cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system.

EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/SYMPTOMS

INHALATION Cough. Headache. Fatigue. Drowsiness.

SKIN Dry skin.

EYES Redness. Pain. Burning.

INGESTION Burning sensation. Headache. Confusion. Dizziness. Unconsciousness.

N O T E S Ethanol consumption during pregnancy may adversely affect the unborn child. Chronic ingestion of ethanol may cause liver cirrhosis.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 39

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Hydrocarbons, C3-4:

Toxicity to daphnia and other aquatic invertebrates

- LC50 Daphnia magna, 48h = 14,22 mg/l (butane)



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

11 / 13

In conformity to Regulation (EU) 2015/830

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:
Toxicity to fish
- LC50 *Oncorhynchus mykiss* (rainbow trout), 96h > 1000 mg/l (literature value)
Toxicity to daphnia and other aquatic invertebrates
- EC50 *Daphnia magna*, 48h = 1000 mg/l
Toxicity to algae
- EC50 *Pseudokirchnerella subcapitata*, 72h > 1000 mg/l (literature value)

ethyl alcohol:
Toxicity to fish
- LC50 *Leuciscus idus*, 48h: 8.140 mg/l
Toxicity to daphnia and other aquatic invertebrates
- EC50 *Daphnia magna*, 24h: 9,3 - 14,2 g/l
Toxicity to algae
- EC50 *Chlorella pyrenoidosa*, 24h > 100 mg/l (literature value)

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Related to contained substances:
Hydrocarbons, C3-4:
1.09 to 2.80 log Pow (liquefied petroleum gas)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 °C can burst.
Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 1950



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

12 / 13

In conformity to Regulation (EU) 2015/830

ADR exemption because compliance with the following characteristics:
Combination packagings: per inner packaging 1 L per package 30 Kg
Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

ADR/RID/IMDG: AEROSOL infiammabili
ADR/RID/IMDG: AEROSOL flammable
ICAO-IATA: AEROSOL flammable

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class: 2
ADR/RID/IMDG/ICAO-IATA: Label: Limited quantities
ADR: Tunnel restriction code: D
ADR/RID/IMDG/ICAO-IATA: Limited quantities: 1 L
IMDG - EmS: F-D, S-U

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: --

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous
IMDG: Marine polluting agent: Not

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions.
The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU, annex I, part 1

Control of Substances Hazardous to Health (COSHH), Regulations 2002

Regulation 2006/1907/EC (REACH), Regulation 2008/1272/EC (CLP).

Seveso category:

P3a - FLAMMABLE AEROSOLS

REGULATION (EU) No 1357/2014 - waste:

HP3 - Flammable

HP5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier



SAFETY DATA SHEET

SUPER HELP - BIKE DEGREASER

Issued on 12/22/2010 - Rel. # 2 on 10/03/2017

13 / 13

In conformity to Regulation (EU) 2015/830

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 1.1. Product identifier, 1.2. Relevant identified uses of the substance or mixture and uses advised against, 2.1. Classification of the substance or mixture, 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 4.1. Description of first aid measures, 4.3. Indication of any immediate medical attention and special treatment needed, 8.1. Control parameters, 8.2. Exposure controls, 10.1. Reactivity, 11.1. Information on toxicological effects, 12.1. Toxicity, 14.2. UN proper shipping name, 14.3. Transport hazard class(es), 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

H220 = Extremely flammable gas.

H280 = Contains gas under pressure; may explode if heated.

H226 = Flammable liquid and vapour.

H304 = May be fatal if swallowed and enters airways.

H336 = May cause drowsiness or dizziness.

H225 = Highly flammable liquid and vapour.

H319 = Causes serious eye irritation.

Classification based on data of all mixture components

Main normative references:

Regulation 1907/2006/EC

Regulation 1272/2008/EC

Regulation (EU) 2015/830

*** This tab annuls and replaces any previous edition.